

# DIFCO BOGMISER



THE MULTI-PURPOSE MACHINE SUITABLE FOR A  
WIDE VARIETY OF ARDOUS TASKS



## *PEAT EXTRUSION PRESS/HOPPER*

### *SPECIAL FEATURES:*

- Very Large Mouth Opening for Easy Filling.
- 1m Diameter Four Stage Mixing Shaft.
- Independently Moving Hopper Doors.
- Floating Peat Extrusion Head — Crocodile Mouth Opening ensures blockages are released quickly.
- Continuous Mixing possible during filling and extrusion.
- Re-circulation Auger aids the mixing process.

### SPECIAL FEATURES

- Multipurpose machine suitable for use in a wide range of arduous conditions (e.g.) peatlands, swamps, forests, etc.
- Capable of carrying out a full range of 3 part linkage operations.
- A very high level of reliability and low ground pressure leads to high output and minimum maintenance.
- Safety Guards fitted to International Safety standards.
- Moving rubber mounted Cab allows for optimum visibility.
- Enclosed vibration damped cab and controls are laid out to ensure maximum operator comfort.
- Filters and other service points are centrally located for ease of service and routine check.
- Sheerbolt mechanism fitted to ensure protection of all components.



The DIFCO BOGMISER can operate a wide range of Ditching Equipment on its 3 pt. linkage.

The 12m<sup>2</sup> Platform of the Bogmiser allows a wide range of Transporting Equipment to be operated.

The BOGMISER can operate a wide range of Forestry equipment such as the DIFCO Mounding Machine and Forestry Ploughs.

The BOGMISER can also be fitted with a Levelling Blade, the powerful hydro static drives, hubs and accurate solenoid operated controls allow perfect levelling to be carried out.

The BOGMISER can effortlessly extrude row after row of a quality mixed peat.



### TECHNICAL DATA:

- Air cooled engine 162 kw (220 hp).
- Hydro static track and p.t.o. drive.
- Track length 5.8m (19 ft.).
- Distance between track centres 2.5m (8 ft.).
- Track Pads width and type to customers specifications.
- A wide range of pads available, Plastic, Smooth Steel and Grouser.
- Low ground pressure — unladen 0.071 kg/cm<sup>2</sup> (1 p.s.i.).
- Powerful Poclain Track Motors.
- Variable Speed Hydro static Drive.

*With continuous improvement we reserve the right to alter or modify without notice, and without obligation on implements purchased before or after changes are made. All weights and measurements in this brochure are approximate.*

Manufactured by

## **Ballintubber Enterprises Ltd.**

Ballintubber, Castlerea, Co. Roscommon, Ireland.

Tel: (0907) 55101/55024. Tel. Int.: 353-907-55024

Fax: (0907) 55102. Telex: 53753 BEL.